

Material Safety Data Sheet

Date last revised : Jan 31, 2003

I. General Information		
Chemical Name & Synonyms: Blend of organic esters and solvent Chemical Family: NA Proper DOT Shipping Name: Petroleum Distillates, N.O.S. Combustible liquid, UN 1268 Manufacturer: FABRICARE INC., Manufacturer's Address: 140 Highland St. Portchester NY 10573	Trade Name & Synonyms: FABRICARE ROYALE Formula: Proprietary Blend DOT Hazard Classification: Combustible liquid Manufacturer's Phone: 914.937.9484 Chemtrec Phone: 800.424.9300	
II. Ingredients		
Principal Hazardous Composition: Petroleum hydrocarbon solvent C.A.S. #8030-30-6	Percent: 50%	Threshold Limit Value (unit) 200ppm HMIS Rating: Health : 2 Flamability : 2 Reactivity: 0
III. Physical Data		
Boiling Point (F): Int, 318° Vapor Pressure (mmHg) < 1mm Hg @25°C Vapor Density (Air =1): Greater than 5 Solubility in Water Not soluble. Appearance & odor : Amber viscous liquid, mild odor.	Specific Gravity (H ₂ O=1): 0.929 Percentage Volatile by Volume (%): 50% Evaporation Rate(_____=1): (Butyl Acetate = 1) < 0.1 Ph: 6.5 - 7.5	
IV. Fire & Explosion Hazard Data		
Flash Point(Test Method): TCC > 170°F Flammable Limits: Air % by vol. Extinguishing Media: Foam, dry chemical, CO ₂ Special Fire Fighting Procedure: Use air supplied breathing equipment for enclosed areas. Cool exposed containers with water spray. Avoid breathing vapor fumes. Unusual fire & Explosion Hazards: Do not mix or store with strong oxidants. COMBUSTIBLE LIQUID. Do not store near sources of ignition.	Auto Ignition Temperature: 420°F LEL 0.6 UEL 7.0	